

DA 5428 W Puristic Arca Wall ventilation hood with energy-efficient LED lighting and backlit controls for easy use.



- Distinctive design 47 1/4 (1198) in (mm) wide stainless steel ventilation hood
- Unique user convenience Con@ctivity
- Energy-efficient and quiet
- Safe and easy to clean Miele CleanCover

EAN: 4002516057390 / Material number: 10934860 / Old Material Number: 28542850USA

EAN: 4002516057390 / Material number: 10934860 / Old Ma	
Design	
Wall ventilation hood	•
Operating modes	
Recirculated mode	Exhaust air
Design	
Color	Stainless steel
RAL colours possible as special order	•
Customization possible on request	•
Variable height available as special order	•
User convenience	
Miele@home	•
Automatic function	Con@ctivity 3.0
Electronic controls	•
Power levels (number excl. Intensive)	3
Miele@mobile app	•
Programmable Intensive switch-off	•
Delayed shutdown for 5 or 15 minutes	•
Grease filter saturation indicator	•
Programmable grease filter saturation indicator	•
Acoustic package	•
CleanCover	•
Filter system	
Number of dishwasher-safe stainless-steel grease filters	4
Lighting	
LED	•
Number x W	4 x 3 W
Number x W  Light intensity in Lx	4 x 3 W 400  x
Light intensity in Lx	400 lx
Light intensity in Lx Color temperature in K	400 lx
Light intensity in Lx Color temperature in K Blower	400 lx 3000 Kelvin
Light intensity in Lx Color temperature in K Blower Dual-action blower AC motor	400 lx 3000 Kelvin
Light intensity in Lx Color temperature in K Blower Dual-action blower AC motor Exhaust air	400 lx 3000 Kelvin
Light intensity in Lx Color temperature in K Blower Dual-action blower AC motor Exhaust air Air throughput	400 lx 3000 Kelvin
Light intensity in Lx Color temperature in K Blower Dual-action blower AC motor Exhaust air Air throughput Safety	400 lx 3000 Kelvin
Light intensity in Lx Color temperature in K Blower Dual-action blower AC motor Exhaust air Air throughput	400 lx 3000 Kelvin
Light intensity in Lx Color temperature in K Blower Dual-action blower AC motor Exhaust air Air throughput Safety Safety shut-off Technical data Overall hood height for vented mode and external in inches	400 lx 3000 Kelvin
Light intensity in Lx Color temperature in K Blower Dual-action blower AC motor Exhaust air Air throughput Safety Safety shut-off Technical data Overall hood height for vented mode and external in inches (mm) Overall hood height for recirculation and external in inches	400 lx 3000 Kelvin   Values upon request
Light intensity in Lx Color temperature in K Blower Dual-action blower AC motor Exhaust air Air throughput Safety Safety shut-off Technical data Overall hood height for vented mode and external in inches (mm) Overall hood height for recirculation and external in inches (mm)	400 lx 3000 Kelvin • • • Values upon request • 29 3/8 (745)–41 5/8 (1055) 34 1/2 (875)–46 3/4 (1185)
Light intensity in Lx  Color temperature in K  Blower  Dual-action blower  AC motor  Exhaust air  Air throughput  Safety  Safety shut-off  Technical data  Overall hood height for vented mode and external in inches (mm)  Overall hood height for recirculation and external in inches (mm)  Overall min. height for vented and external in in. (mm)	400 lx 3000 Kelvin  Values upon request  29 3/8 (745)–41 5/8 (1055)  34 1/2 (875)–46 3/4 (1185)  29 3/8 (745)
Light intensity in Lx  Color temperature in K  Blower  Dual-action blower  AC motor  Exhaust air  Air throughput  Safety  Safety shut-off  Technical data  Overall hood height for vented mode and external in inches (mm)  Overall hood height for recirculation and external in inches (mm)  Overall min. height for vented and external in in. (mm)  Canopy width in in.(mm)	400 lx 3000 Kelvin  Values upon request  29 3/8 (745)–41 5/8 (1055)  34 1/2 (875)–46 3/4 (1185)  29 3/8 (745)  47 1/4 (1198)
Light intensity in Lx  Color temperature in K  Blower  Dual-action blower  AC motor  Exhaust air  Air throughput  Safety  Safety shut-off  Technical data  Overall hood height for vented mode and external in inches (mm)  Overall hood height for recirculation and external in inches (mm)  Overall min. height for vented and external in in. (mm)  Canopy width in in.(mm)  Overall max. height for vented and external in in. (mm)	400 lx 3000 Kelvin  Values upon request  29 3/8 (745)–41 5/8 (1055)  34 1/2 (875)–46 3/4 (1185)  29 3/8 (745)  47 1/4 (1198)  41 5/8 (1055)
Light intensity in Lx  Color temperature in K  Blower  Dual-action blower  AC motor  Exhaust air  Air throughput  Safety  Safety shut-off  Technical data  Overall hood height for vented mode and external in inches (mm)  Overall hood height for recirculation and external in inches (mm)  Overall min. height for vented and external in in. (mm)  Canopy width in in.(mm)  Overall max. height for vented and external in in. (mm)  Canopy height in in.(mm)	400 lx 3000 Kelvin  Values upon request  Values upon request  29 3/8 (745)–41 5/8 (1055)  34 1/2 (875)–46 3/4 (1185)  29 3/8 (745)  47 1/4 (1198)  41 5/8 (1055)  4 3/4 (120)
Light intensity in Lx Color temperature in K Blower Dual-action blower AC motor Exhaust air Air throughput Safety Safety shut-off Technical data Overall hood height for vented mode and external in inches (mm) Overall hood height for recirculation and external in inches (mm) Overall min. height for vented and external in in. (mm) Canopy width in in.(mm) Overall max. height for vented and external in in. (mm) Canopy height in in.(mm) Overall min. height for recirculation in in. (mm)	400 lx 3000 Kelvin  Values upon request  Values upon request  29 3/8 (745)–41 5/8 (1055)  34 1/2 (875)–46 3/4 (1185)  29 3/8 (745)  47 1/4 (1198)  41 5/8 (1055)  4 3/4 (120)  34 1/2 (875)
Light intensity in Lx Color temperature in K Blower Dual-action blower AC motor Exhaust air Air throughput Safety Safety shut-off Technical data Overall hood height for vented mode and external in inches (mm) Overall hood height for recirculation and external in inches (mm) Overall min. height for vented and external in in. (mm) Canopy width in in.(mm) Overall max. height for vented and external in in. (mm) Canopy height in in.(mm) Overall min. height for recirculation in in. (mm) Canopy depth in in.(mm)	400 lx 3000 Kelvin  Values upon request  Values upon request  29 3/8 (745)–41 5/8 (1055)  34 1/2 (875)–46 3/4 (1185)  29 3/8 (745)  47 1/4 (1198)  41 5/8 (1055)  4 3/4 (120)  34 1/2 (875)  20 1/2 (520)
Light intensity in Lx Color temperature in K Blower Dual-action blower AC motor Exhaust air Air throughput Safety Safety shut-off Technical data Overall hood height for vented mode and external in inches (mm) Overall hood height for recirculation and external in inches (mm) Overall min. height for vented and external in in. (mm) Canopy width in in.(mm) Overall max. height for vented and external in in. (mm) Canopy depth in in.(mm) Overall min. height for recirculation in in. (mm) Canopy depth in in.(mm) Overall max. height for recirculation in in. (mm)	400 lx 3000 Kelvin  Values upon request  Values upon request  29 3/8 (745)–41 5/8 (1055)  34 1/2 (875)–46 3/4 (1185)  29 3/8 (745)  47 1/4 (1198)  41 5/8 (1055)  4 3/4 (120)  34 1/2 (875)  20 1/2 (520)  46 3/4 (1185)
Light intensity in Lx Color temperature in K Blower Dual-action blower AC motor Exhaust air Air throughput Safety Safety shut-off Technical data Overall hood height for vented mode and external in inches (mm) Overall hood height for recirculation and external in inches (mm) Overall min. height for vented and external in in. (mm) Canopy width in in.(mm) Overall max. height for vented and external in in. (mm) Canopy height in in.(mm) Overall min. height for recirculation in in. (mm) Canopy depth in in.(mm) Overall max. height for recirculation in in. (mm) Minimum height above electric hobs in mm Minimum height above gas hobs (max. 12.6 kW total	400 lx 3000 Kelvin  Values upon request  Values upon request  29 3/8 (745)–41 5/8 (1055)  34 1/2 (875)–46 3/4 (1185)  29 3/8 (745)  47 1/4 (1198)  41 5/8 (1055)  4 3/4 (120)  34 1/2 (875)  20 1/2 (520)
Light intensity in Lx Color temperature in K Blower Dual-action blower AC motor Exhaust air Air throughput Safety Safety shut-off Technical data Overall hood height for vented mode and external in inches (mm) Overall hood height for recirculation and external in inches (mm) Overall min. height for vented and external in in. (mm) Canopy width in in.(mm) Overall max. height for vented and external in in. (mm) Canopy depth in in.(mm) Overall min. height for recirculation in in. (mm) Overall max. height for recirculation in in. (mm) Canopy depth in in.(mm) Overall max. height for recirculation in in. (mm) Minimum height above electric hobs in mm	400 lx 3000 Kelvin  Values upon request  Values upon request  29 3/8 (745)–41 5/8 (1055)  34 1/2 (875)–46 3/4 (1185)  29 3/8 (745)  47 1/4 (1198)  41 5/8 (1055)  4 3/4 (120)  34 1/2 (875)  20 1/2 (520)  46 3/4 (1185)  24 1/8 (610)



DA 5428 W Puristic Arca Wall ventilation hood with energy-efficient LED lighting and backlit controls for easy use.




EAN: 4002516057390 / Material number: 10934860 / Old Material Number: 28542850USA

Length of electrical wire in ft (m)	2 (0.8)
Standard plug fitted	•
Total connected load in kW	0.36
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Frequency in Hz	60
Installation note	
Vent connection at top	•
Vent connection at top and rear	•
Diameter of vent connection in in.(mm)	6 (150)
Telescopic chimney	•
Standard accessories	
Reducer from 150 to 125 mm Ø	•
Non-return flap	•
Optional accessories	
OdorFree charcoal filter	Nein



DA 5428 W Puristic Arca Wall ventilation hood with energy-efficient LED lighting and backlit controls for easy use.



DA 5428 W(Installation drawing)

1) and 2) Shaded area for vent cut-out