



# FF195CSSIF



34" x 19" x 18" (H x W x D)

Commercially approved, ENERGY STAR certified all-refrigerator for built-in or freestanding use with a shallow 18" depth, panel-ready door, and stainless steel cabinet

**Highlights:**

18" shallow depth makes it ideal for smaller commercial and residential settings

ENERGY STAR certified performance ensures annual savings

Panel-ready door lets you create the perfect look

**Product Features:**

|                                  |                                                                                                                                                                                                                                                                             |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 18" shallow depth                | Ideal for home wet bars, island kitchens, and other applications with limited footprint space                                                                                                                                                                               |
| ENERGY STAR certified            | Rated by the DOE to perform with more efficiency than federal standards require, saving your unit energy and you on higher utility costs                                                                                                                                    |
| Commercially approved            | ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings                                                                                                                                                                                              |
| Panel-ready door                 | Integrated stainless steel door frame accepts full overlay panels, allowing you to customize the refrigerator door or blend it into your cabinetry design; panel size: 18 7/8" W x 31 9/16" H and at least 3/4" thick; 10 lbs. maximum; customers provide their own handles |
| Stainless steel wrapped exterior | Cabinet features 304 grade stainless steel construction for added durability and a professional look                                                                                                                                                                        |
| Built-in capable                 | Front-breathing design lets you make the best use of space by installing your appliance under the counter                                                                                                                                                                   |
| Automatic defrost                | Reduced user maintenance with auto defrost system                                                                                                                                                                                                                           |
| Adjustable shelves               | Three glass shelves with brake system ensures safe, optimal storage                                                                                                                                                                                                         |
| Door racks                       | Two chrome racks accommodate a variety of sizes for optimal interior storage                                                                                                                                                                                                |



FF195CSSIF Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Height of Cabinet          | 34.0" (86 cm)      |
| Width                      | 19.0" (48 cm)      |
| Depth                      | 18.0" (46 cm)      |
| Depth with door at 90°     | 35.0" (89 cm)      |
| Capacity                   | 3.13 cu.ft. (89 L) |
| Defrost Type               | Automatic          |
| Door                       | Panel-Ready        |
| Cabinet                    | Stainless Steel    |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Sanitation                 | ETL-S              |
| Energy Usage/Year          | 259.0kWh/year      |
| Amps                       | 1.3                |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 80.0 lbs. (36 kg)  |
| Parts & Labor Warranty     | 1 Year             |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101075075       |
| Refrigerator Features      |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Height Adjustable          | Yes                |
| Shelf Type                 | Glass              |
| Shelf Qty                  | 3                  |
| Adjustable Shelves         | Yes                |
| Thermostat Type            | Dial               |
| Fan Type                   | Interior           |
| Refrigerant Type           | R600a              |
| Refrigerant Amount         | 0.88oz.            |
| High Side PSI              | 320.0              |
| Low Side PSI               | 120.0              |
| Level Legs Qty             | 2                  |
| Interior Light             | Yes                |
| Temperature Range          | 34 to 50°F         |
| Sound Level                | 33.4 dB            |
| Dimensions                 |                    |
| Interior Height            | 29.0" (74 cm)      |

|                        |                |
|------------------------|----------------|
| Interior Width         | 16.0" (41 cm)  |
| Interior Depth         | 12.75" (32 cm) |
| Compressor Step Height | 7.0" (18 cm)   |
| Compressor Step Width  | 16.0" (41 cm)  |
| Compressor Step Depth  | 6.25" (16 cm)  |

