24" Built-In Dishwasher with EvenDry™ System

Dishwasher

Available Products: FPID2498SF

Available Colors: Stainless Steel

Version: 07/23

Product Specifications

Dishwasher

Automatic Temperature Control	No
Filter Material	Stainless Steel
Filter Trap	Removable
Hard Food Disposer or Filtration	Yes
Interior Light	No
Motor Speeds	Multi-Speed
Place Setting Capacity	14
Rinse Aid Dispenser	Yes
Smart Soil Sensor	Yes
Lower Spray Arm	Orbit
Middle Spray Arm	Bi-Beam
Upper Spray Arm	Spray Arm
Tub Design	Tall Tub
Tub Material	Stainless Steel
Wash Levels	5
Wash System	Direct Feed
Water Pressure	90 psi
Water Usage	8 Gallons

Dishwasher Options

Drying System	Even Dry
Heated Dry	Yes
High Temperature	Yes

Upper Rack

Cup Shelf	Yes
Fold-Down	Yes
Stemware Holder	Yes

Controls

Delay Start Hours	1-24 Hours
Digital Display	Yes
Control Lock	Yes

Dimensions and Volume

Minimum Height	33 3/4"
Maximum Height	35 3/4"
Width	23 3/4"
Depth	24 1/4"
Depth With Door Open	50 1/4"

Dishwasher Cycles

China Crystal	Yes
Energy Saver	Yes
Favorite	Yes
Heavy	Yes
Normal	Yes
Number of Cycles	7
Quick	Yes
Rinse Only	Yes

Lower Rack

Fold-Down	Yes
Maximum Height Clearance	13"
Minimum Height Clearance	11"
Number of Silverware Basket	1
Number of Silverware Basket Lids	3

Third Level Rack

Rack Handles	Yes

Exterior

Door and Handle Design	Handle
Door Latch	Pull
Door Type	StayPut

Electrical Specifications

Voltage Rating	120 V

General Specifications

Sound Level	47 dBA
Annual Energy	240 kWh
Prop 65 Label	No
Warranty - Labor	1 Year
Warranty - Parts	1 Year

Performance Certifications and Approvals

CEE Tier	Tier 1
ENERGY STAR Certified	Yes

Installation

Connection Location	Right Bottom
Number of Leveling Legs	3
Water Inlet Location	Left Bottom Front

Certifications and Approvals

ADA Compliant	No

Safety Certifications and Approvals

UL Listed	Yes
ETL Listed	No
Meets ASSE 1006 Requirements	Yes
NSF Certified	Yes

Installation Diagram

Front

23¾"

33¾"
Adjustable
to 35¾"*

*Height only adjustable to 35¾" max. when installed in 35¾" max. standard cabinetry cutout. (Dimensions do NOT include insulation – insulation blanket may be compressed during installation.)

Left

24¼"

Right

50¼"

22½"

Door in 90° open position

27¾"

Power supply & water inlet location (bottom rear)

90°

34" min. to 35¾" max.**

24" min.

3"

3½" min. to 4½" max.

1¼"

2¼"

Electrical, water, and drain lines must be confined to shaded area

Preferred drain areas

3"

90°

18"

3"

**NOTE: 35¾" max. height for standard cabinetry cutout. (5/16" min. clearance required from unit to underside of countertop.)

1"

2¼"

24"