



**24" ADA-COMPLIANT SERIES**  
*Freezer Drawers*



**eco**friendly  
R600a Refrigerant



JOB	
AREA	
ITEM NO.	
MODEL NO.	



Drawer Model

MODELS	DESCRIPTION
<b>HA24FB-4-5</b>	Indoor ADA Freezer Drawers Stainless Steel Drawers
<b>HA24FB-4-6</b>	Indoor ADA Freezer Drawers Panel Ready Drawers

**KEY PRODUCT FEATURES AND BENEFITS**

- Industry's largest selection of ADA compliant models for accessible and aging in place designs
- 800 BTU/hr capacity delivers commercial grade cooling performance
- Variable speed compressor minimizes sound; up to 30% quieter than competitors
- Commercial-grade all stainless steel interior provides superior durability and easy cleaning; black vinyl exterior for built in applications

**Quick Features:**

- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready door to match your design style
- Audible door alarm warns user if door is held open
- White LED task lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Smooth glide self-closing drawers offer high storage capacity



**24" ADA-COMPLIANT SERIES**  
Freezer Drawers

MODEL NUMBERS		HA24FB
MODEL DESCRIPTION		24" ADA Compliant Freezer Drawers
ATTRIBUTES		
Perlick Anti-Condensation System		NO
OVERALL DIMENSIONS	Width - in. (mm)	23-7/8" (606 mm.)
	Depth - in. (mm)	24" (610 mm.)
	Height - in. (mm)	32" (813 mm.)
OPENING DIMENSIONS	Width - in. (mm)	24" (610 mm.)
	Depth - in. (mm)	24-7/8" (632 mm.)
	Height - in. (mm)	32-1/4" (819 mm.)
INTERNAL VOLUME Net. Cu. Ft.		4.6 cu. ft total
SHIPPING WEIGHT Lbs. (kg.)		181 lbs (82.27 kg.)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph
	Running Load Amps	2.2 amps
	Electrical Connection	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P
	Cord Length	6'
	Defrost Initiation	Time
	Defrost Type	Hot Gas
	Thermostat	Digital
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a (57g)
	Expansion Device	Capillary Tube
	Temperature Settings F°(C°)	-10° (-23.3°) - 10° (-12.2°) <b>Factory Set Point 0° (-17.8°)</b>
	Heat Rejection (at 75°F)	700 BTU/hr
	Pull Down Capacity	800 BTU/hr
	Front Vented	Yes
PLUMBING		None Required

*Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.*

**ACCESSORIES**

MODEL NOS.	DESCRIPTION
(DL)	Factory Installed Lock
67969	24" Stainless Steel Drawer Dividers
66736	Caster Kit for HP24/HC24/HA24 models
RK24DP	24" Drawer Prep Station Tray

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit [perlick.com](http://perlick.com).



**24" ADA-COMPLIANT SERIES**  
Freezer Drawers

CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HA24FB-4-5	HA24FB4B-00-EDF0D	Drawers	No
HA24FB-4-6	HA24FB4B-00-DD00D	Drawers	No
HA24FB-4-5DL	HA24FB4B-00-EDFLD	Drawers	Yes
HA24FB-4-6DL	HA24FB4B-00-DD0LD	Drawers	Yes

50" [1270] AREA IN WHICH ELECTRICAL OUTLET MUST BE LOCATED

