REF30PRR

REFRIGERATOR 30" BUILT-IN BOTTOM MOUNT PANEL READY RIGHT SWING DOOR





True flush installation with proprietary 'Lift & Swing' hinges, ensuring perfect door balance and requiring minimal clearance from adjacent cabinets

All metal construction inside and out for longer durability and optimized insulation for max cold retention

Precise temperature control for optimal food preservation: lateral airflow system, powered by dual variable-speed compressors and dual evaporators, reduces cold loss when opening door

FlexMode control to set temperature in lower compartment as Freezer (<32F), Fresco (30-34F) or Fridge (38-42F)

Automatic custom ice maker with control over ice cube size

Integrated water filter located in the low temperature section ideal for hygienically clean drinking water and ice

Digital LED touch interface with user-friendly controls for temperature, humidity, speed-freeze and ice making


PRODUCT FEATURES	
Style	Panel ready bottom mount
Interior finish	White aluminum
User interface	Digital LED touch interface
Lighting	Top and sidewall LED lights
Refrigerator shelves	2 full-width and height-adjustable
Refrigerator crispers	2 soft-close metal drawers
Freezer compartment	FlexMode control to set temperature as Freezer (-32F), Fresco (30-34F) or fridge (38-42F)
Door storage	3 height-adjustable bins
Ice maker	Automatic with customizable ice cube size producing up to 3 lbs/24 hr
Programs	Max Cool Fridge- Super-Ice - Beverage Cooler - Ice Size - Sabbath Mode Vacation Mode
INTERIOR CAPACITY	
Total volume	14 cu.ft
Refrigerator	11 cu.ft
Freezer	3 cu.ft
TECHNICAL SPECIFICAT	IONS
Voltage, Frequency, Amps	115V 60 Hz - 5 Amps 550W
DOE Compliant	YES - 580 kWh/yr
Power connection	120V 3-prong plug with 98" cord
Water connection	1/4" waterline with accessible shut-off valve
Water supply pressure	Min 0.05 MPa (0.5Bar) Max 0.5 MPa (5 Bar)
Certification	ETL
Warranty	2 years parts & labor 5 years parts & labor for sealed system
Packaging dimensions and weight	W 31 1/2" H 89" D 31 1/2" Weight 606 lbs
ACCESSORIES	
901469	Connection trim for side-by-side installation of panel ready built-in refrigerators
Z310001	Replacement water filter


REF30PRR

REFRIGERATOR 30" BUILT-IN BOTTOM MOUNT PANEL READY RIGHT SWING DOOR




SIDE











25"

+1" for the adjustable max height of the leveling feet

CUTOUT DIMENSIONS




SIDE BY SIDE INSTALLATION




Keep open for Power cord and Water line

WATER & ELECTRIC LINES:

Both lines are located at the back base of the unit. This area is 8" high and 2" deep, which allows lines to be run to their service locations. These service locations should be off to either side of the unit. Both lines are 98 3/8" long.





WATER HOOKUP:

Unit comes with 1/4" to 3/4" elbow adapter. Use John Guest quick connect (push fitting) 1/4" to 3/4" metric threaded NPT. Standard GHT (Ex: stainless braided) cannot be substituted due to risk of cross threading

