

SV6

LIGHT COMMERCIAL COIN DROP FRONT CONTROL STACK WASHER-DRYER

Built for Reliable Performance

Engineered and built like no other, the Speed Queen® coin drop front load washer and dryer are designed for performance and reliability. Our commercial-grade construction is rugged, dependable, and built to last. Plus, property owners can rely on the practical ingenuity of features designed to make their lives simpler and more productive.



SV6 Control Panel

Washer:

- Revolutionary balancing technology redistributes and balances even the most unbalanced loads
- Increased 440 G-Force extraction speed reduces drying times
- Durably designed to deliver long-lasting performance with features like a rugged suspension system, stainless steel wash tub and dynamic balancing system
- ADA Compliant

Dryer:

- Door is reversible for installation flexibility
- High efficiency exhaust blower with superior airflow 220 cfm (105 liters/sec)
- 100% serviceable from the front
- Efficient and fast dry cycle



LIGHT COMMERCIAL COIN DROP FRONT CONTROL STACK WASHER-DRYER



SV6

Product Code	Gas: SV6000WG Electric: SV6000WE	
	Washer	Dryer
Color	White	
Capacity - lb (kg)	21 (9.5)	18 (8.2)
Cylinder Volume - cu.ft. (liters)	3.42 (96.8)	7.0 (198)
Spin Speed G-Force (RPM)	440 (1200)	-
Motor Size - HP	0.9	0.33
Type of Gas (Gas Models Only)	-	Factory Equipped Natural
Water Consumption Per Cycle - g (liter)*	13.68 (51.8)	-
IWF (Water Factor) - gal/ft ³ (liters/liter/cycle)*	4.0 (0.53)	-
MEF ₃₂ (Modified Energy Factor) ft ³ /kWh/cycle (Liters/kWh/cycle)*	2.20 (62.3)	-
Available Water Temperatures	Cold, Warm, Hot	-
Available Cycles	Normal, Synthetic, Delicate	High, Medium, Low, Delicate, No Heat
Air Outlet Diameter - in	4	
Exhaust Airflow - cfm (liters/sec)	220 (105)	
Electrical Requirements (v/Hz/Ph-Amp)	**Electric Gas	120/60/1 - 15 Amp 120/208/240/60/1-30 Amp 120/60/1-15 Amp
Heating Element	Electric Gas	- 5350W, 240V / 4750W, 208V 25,000 Btu
Net Weight - lb (kg)	385 (175)	
Shipping Weight - lb (kg)	417 (189)	
Shipping Dimensions Approx. - in	Width	34
	Depth	30
	Height	80
Agency Approvals	cULus, ENERGY STAR® certified	
Model No.	STENCASP176TW01 STGNCASP116TW01	

Dimensions	Width - in	Height - in	Depth - in	Floor to Door Opening - in	Door Swing - in
SV6000WE/ SV6000WG	26.875	78.17	31.27	14.6***	24

Required Coin Kits (sold separately)
Coin Box – Model #: CK043 (2 required)

For Commercial Use Only

Note: Stack washer-dryer requires two power cords. One for washer, one for dryer.

* Average usage based on multiple load sizes and current DOE test protocol. Real usage will vary depending on load size, composition and cycle selectivity.

** Electric dryers are dual rated for 208-240V applications. Using dryer in 208V will reduce the wattage output. An optional kit (61928) can be used to field convert the unit for 4750 output at 208V.

Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

*** For ADA compliance turn legs out from base 0.5 inches

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.

AR22-0039

Speed Queen by Alliance Laundry Systems