



Color Variants

VI230620
Black control panel
Width 12"

Included accessories
1 x glass scraper.

Optional accessories
GP900001
Stainless steel frying sensor pan.
GP900002
Stainless steel frying sensor pan.
GP900003
Stainless steel frying sensor pan.
VD200020
Black appliance cover

Installation Accessories
VV200010
Stainless steel connection strip
for combination with further Vario
cooktops
VV200020
Black connection strip for combination
with other Vario appliances of the 200
series

VI230620
Vario induction cooktop 200 series
Black control panel
Width 12"

Can be combined with cooktops of
the Vario 200 series to a harmonic
unity
Control panel for comfortable and
secure operation

Cooking zones
1 induction cooking zone ø 9" (2200 W,
with booster 3700 W).
1 induction cooking zone ø 6" (1400 W,
with booster 1800 W).

Operation
Control knobs with illuminated ring.
Integrated control panel.
Electronic power control in 17 output
levels.

Features
Cooking zone marking.
Frying sensor function.
Pot detection.
Booster function for both cooking
zones.

Safety
Residual heat indicator.
Operation indicator.
Safety shut-off.

Planning notes
Operates with magnetic (induction)
iron pots and pans only. For an optimal
heat distribution, the use of flat bottom
cookware is recommended.
Appliance can be snapped into the
countertop from above.
Appliance weight: approx. 15.4 lbs (7
kg).

Rating
Total rating: 208/220 - 240 V : 10.8 kW.
60 Hz
Plan for a 37" connecting cable
without plug (hardwire required).

Product Features
Product name / series name
Vario/Domino cooking zone cera
Construction type
CONSTR_TYPE.Built-in
Energy source
Electric
Total number of cooktop burners
2
Required cutout size (HxWxD) (mm)
125 x 268 x 492
Width of the product (mm)
288
Overall appliance dimensions (HxWxD)
(mm)
125 x 288 x 512
Product packaging dimensions
(HxWxD) (mm)
200 x 400 x 600
Net weight (kg)
6.595
Gross weight (kg)
7.7
Residual heat indicator
Separate
Location of control panel
Cooktop front
Basic surface material
Ceramic
Color of surface
Black, Stainless steel
Color of frame
Stainless steel
Approval certificates
CSA, FCC
Power cord length (cm)
96

Consumption and connection features
Watts (W)
3700
Gas connection rating (W)
Current (A)
Volts (V)
208-240
Frequency (Hz)
60

2019-11-04
Page 1

